

DSE8003 MKII

7" COLOUR MULTI-SET REMOTE OVERVIEW DISPLAY



KEY FEATURES

- Multiple modules (max 20) within the same load sharing system can be viewed on the 8003's front screen.
- Touch-screen enabled.
- RS232, RS485 and Ethernet communications.
- Audible alarm.
- Front panel mounting.
- Protected front panel configuration.
- Remote monitoring.
- System monitoring.
- Enhanced graphical user interface.
- Powerful processor for fast operating response times.

KEY BENEFITS

- Compatible with DSE86XX MKII load share modules.
- Data communication link allows remote system management.
- 800 x 480 pixels for high screen resolution.

SPECIFICATIONS

DC SUPPLY

CONTINUOUS VOLTAGE RATING
8 V to 35 V continuous

CRANKING DROPOUTS

Able to survive 0 V for 50 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries

MAXIMUM OPERATING CURRENT

300 mA at 12V, 150 mA at 24V

OUTPUTS

ALARM OUTPUTS C & D
2 A DC at supply voltage

DIMENSIONS

OVERALL

310 mm x 160 mm x 40 mm
12.2" x 6.3" x 1.5"

PANEL CUTOUT

282 mm x 136 mm
11.1" x 5.3"

OPERATING TEMPERATURE RANGE

-30 °C to +70 °C
-22 °F to +158 °F

STORAGE TEMPERATURE RANGE

-40 °C to +85 °C
-40 °F to +185 °F

RELATED MATERIALS

TITLE	PART NO.
DSE8003 MKII Installation Instructions	053-231
DSE8005 SCADA Suite Manual	057-128
DSE8610 MKII Data Sheet	055-204
DSE8660 MKII Data Sheet	055-169

PART NO.

053-231
057-128
055-204
055-169

DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH
TELEPHONE +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303
EMAIL sales@deepseapl.com **WEBSITE** www.deepseapl.com

DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA
TELEPHONE +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708
EMAIL sales@deepseausa.com **WEBSITE** www.deepseausa.com

DSE8003 MKII

7" COLOUR MULTI-SET REMOTE OVERVIEW DISPLAY

The DSE8003 MKII is designed for use with the DSE86xx MKII load share control modules, giving a choice of display options suitable for a wide variety of applications. One (1) DSE8003 MKII module can be connected to multiple compatible modules via a data communication link up to a maximum distance of 1.2 km in length, using RS485.

The DSE8003 MKII features completely re-designed screen layouts and icons to provide comprehensive large screen graphs, charts, metering, power display and engine status information in a clear image and text format.

The DSE8003 MKII also features an improved processor for improved operating response times.

ENVIRONMENTAL TESTING STANDARDS

ELECTRO MAGNETIC COMPATIBILITY

BS EN 61000-6-2
EMC Generic Immunity Standard for the Industrial Environment
BS EN 61000-6-4
EMC Generic Emission Standard for the Industrial Environment

ELECTRICAL SAFETY

BS EN 60950
Safety of Information Technology Equipment, including Electrical Business Equipment

TEMPERATURE

BS EN 60068-2-1
Ab/Ae Cold Test -30°C
BS EN 60068-2-2
Bb/Be Dry Heat +70°C

VIBRATION

BS EN 60068-2-6
Ten sweeps in each of three major axes
5Hz to 8Hz @ +/-7.5mm, 8Hz to 500Hz @ 2gn

HUMIDITY

BS EN 60068-2-30
Db Damp Heat Cyclic 20/55°C @ 95% RH
48 Hours
BS EN 60068-2-78
Cab Damp Heat Static 40°C @ 93% RH
48 Hours

SHOCK

BS EN 60068-2-27
Three shocks in each of three major axes
15gn in 11mS

DEGREES OF PROTECTION PROVIDED BY ENCLOSURES

BS EN 60529 IP65 - Front of module when installed into the control panel with the supplied sealing gasket.

COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF LOAD SHARE APPLICATIONS

